Available in size: 1/2", 3/4", 1", 11/4", 11/2", 2", 21/2", 3". 4", 5", 6"

Material of Body: Brass

Aluminum

Stainless Steel (By Investment Cast)

## CAM & GROOVE COUPLINGS FOR HOSE & PIPE






**Buna N:** Buna N is standard. It is generally recommended for petroleum derivates, neutral or slightly acidic salt solutions, alcohols, ethers, glycols, fats, oils, and greases. This compound should give good service from -40°F to +250°F.

Neoprene: Recommended for alkaline and acid salt solutions and aldehydes such as formaldehyde. For food service. White neoprene is also available. Temperature recommended -40°F to +250°F.

## TWO LUG UNIVERSIAL CROWFOOT HOSE COUPLINGS (FOR AIR HOSE) TWO SEALS IN ONE MAKE COUPLING AN EASY TASK



MALE THREAD END Size From 1/4" - 2"



HOSE END Size From 1/4 \* - 2\*



FEMALE THREAD END Size From 1/4" - 2 "



THREE - WAY CONNECTION



MALE PIPE( N.P.T. )STEM Size From 1/2" - 4"



HOSE STEM WITH WING NUT & FEMALE SPUD Size From 1/2" - 4"



HOSE MENDERS Steel, Plated Size From 1/2" - 8 \*



COMBINATION HOSE SHANK NIPPLES Steel, Plated Or Plain Size From 1/2" - 10 "



SUCTION HOSE COUPLING Brass Hose Shank, Aluminum Hose Shank With Brass Pin Lug Swivel Size From 1/2" - 6"



HOSE COUPLINGS (FOR SANDBLAST HOSE) Brass, Aluminum Size From 3/4" - 2"



DOUBLE BOLT CLAMP Size From 1/2" - 12"



(C.C.

HOSE CLAMP WITH SAFETY CLAW Size From 1/2" - 4"